Cornelius.

Titan_S



FEATURES

Merchandising

Large and interchangeable LED illuminated graphic for maximum impact. LED lit flavor cards for brand visibility.

Excellent performance

Optimized ice bank and product delivery system ensuring in-spec drink dispense in D condition.

Life cost savings

Optimum air flow control, increased insulation, efficient heat exchange to energy efficiency and prolonged component life time.

Ease of service

Independent refrigeration deck for easy service and maintenance. Structure design allows quick access to key components

Beverage flexibility

Quick hand operated changeover manifold without need for tools and plumbing.

Reliability & Sustainability

R290 green refrigerant and global agency (*CE- need application, ETL Sanitation, GB)

Cornelius,



TECHNICAL SPECIFICATIONS

TYPE OF VALVES	SFV/LEV	ELECTRICAL REQUIREMENTS	230V/50Hz
QTY OF VAVLES	6		2004/00112
		MATERIAL	
CONTINOUS DRAW CAPAC	TY at 12oz, 2 drinks/m	Housing	Painting Steel
D @105°F (40.6°C) 75%RH	65cups	Coil	SS 304
C @90°F (32.2°C) 65%RH	130cups		
B @75°F (23.9°C) 45%RH	280cups	COMPRESSOR SIZE	1/3+HP
WATER BATH SIZE	48L	REFRIGERANT	R290
		PRODUCT WEIGHT	80KG
ICE BANK WEIGHT	12KG		
		AGENCY LISTINGS	CE (need application)
DIMENSIONS (mm)	720(H)*460(W)*743(D)		ETL Sanitation
DIMENSIONS (inch)	28.3(H)*18.1(W)*29.3(D)		GB

Cornelius.

© China | CORNELIUS @2022

Cornelius (Tianjin) Co., LTD No.12, Xintai Road, TEDA, Tianjin, China Tel: +86 22 25290858/Fax: +86 22 25290865 E-mail: customerservice@cornelius.com.cn Website: www.cornelius.com